

Print date: 02/03/2016 Page 1

Revised:23.07.2015

Cimco-Werkzeugfabrik Carl Jul. Müller GmbH & Co. KG

1. DESIGNATION OF THE MATERIAL OR MIXTURE AND COMPANY NAME

1.1 Product identifier

Product name Trade name CAS No. EC No. Allround spray W 44 T, 400ml, 50ml Art. No. **151120 / 151122** Allround spray W 44 T, 400ml, 50ml Art. No. **151120 / 151122**

1.2 Relevant identified use of material or mixture and uses that are not advisable

Recommended limitations of the application

Use of the material/mixture

Technical aerosols

1.3 Details on the supplier who is making the safety data sheet available

Company Cimco Werkzeugfabrik Carl Jul. Müller GmbH & Co. KG

Hohenhagener Straße 1 - 5 D-42855 Remscheid, Germany

+49 (0) 21913718-01 Fax: +49 (0) 21913718-86

1.4 Emergency number Emergency CONTACT (24-Hour-Number)

GBK GmbH +49 (0)6132-84463

2. POSSIBLE HAZARDS

2.1 Classification of the material

· Classification in accordance with the directive (EC) No. 1272/2008 [CLP/GHS]

Aerosol 1 H222. H229, STOT SE 3 H336



Print date: 02/03/2016 Page 2

Revised:23.07.2015

Cimco-Werkzeugfabrik Carl Jul. Müller GmbH & Co. KG

2.2 Label elements

Labelling according to directive (EC) No. 1272/2008 [CLP/GHS]





GHS02

GHS07

Signal word:

Hazard

Hazard warnings:

H222 Extremely inflammable aerosol.

H229 Pressurised container: could burst if heated. H336 May cause drowsiness and dizziness.

Safety information:

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames, and other sources

of ignition. Do not smoke.

P211 Do not spray against open flames or other sources of ignition.

P251 Do not puncture or incinerate, even after use.

P261 Avoid breathing in dust/smoke/gas/mist/vapour/aerosol.

P271 Only use outdoors or in well ventilated rooms.

P304 + P340 IN THE EVENT OF INHALATION: Move the person into fresh air and

ensure they can breathe unrestrictedly.

P312 In the event of feeling unwell, call the POISON CONTROL CENTRE/doctor.

P403 + P235 Store in a cool, well ventilated place.

P405 Keep it locked away.

P410 + P412 Protect against direct sunlight and do not expose to temperatures above

50°C.

P501 Dispose of content/container as problem waste.

2.3 Other dangers

If used extensively, a flammable / combustible mixture of vapour and air can be formed.



Print date: 02/03/2016 Page 3

Revised:23.07.2015

Cimco-Werkzeugfabrik Carl Jul. Müller GmbH & Co. KG

· Results of the PBT and vPvB assessment

 PBT: The materials in the mixture do not meet the PBT/vPvB criteria according to REACH, Appendix XIII.

· vPvB: not applicable

3. COMPOSITION / INFORMATION ON COMPONENTS

Constituents	EC No.	CAS No.	Concentrate [% by weight]
1,2,4-trimethyl benzene	202-436-9	95-63-6	0.1 - 0.29 %
			Flam. Liq. 3, H226
			Acute Tox. 4, H332
			Eye Irrit. 2, H319
			STOT SE 3, H335
			Skin Irrit. 2,H315
			Aquatic Chronic 2, H411
Butane	203-448-7	106-97-8	10 - 24.99 %
			Flam. Gas 1, H220
			Compressed gas
Naphtha (crude oil), heavy	265-150-3	64742-48-9	25-49.99
hydrogen-			Flam. Liq. 3, H226
treated			Asp. Tox. 1, H304
			STOT SE 3, H336
			EUH066
Alkaryl polyether	Polymer		0.3 - 0.99 %
			Eye Irrit. 2, H319
			Skin Irrit. 2, H315
			Aquatic Chronic 2, H411
Propane	200-827-9	74-98-6	3 - 9.99
			Flam. Gas 1, H220
			Compressed gas
Mineral oil			3 - 9.99
			Asp. Tox. 1, H304



Print date: 02/03/2016 Page 4

Revised:23.07.2015

Cimco-Werkzeugfabrik Carl Jul. Müller GmbH & Co. KG

4. FIRST AID MEASURES

4.1 Description of first aid measures

General information Remove dirty, saturated clothing immediately.

After inhaling Ensure there is fresh air.

In the event of complaints, seek medical assistance.

After skin contact In the event of skin contact, rinse off with water.

In the event of long-term skin irritation, consult doctor.

After swallowing Do not induce vomiting

Seek medical assistance.

After eye contact In the event of contact with the eyes, rinse thoroughly with lots of

water and consult a doctor.

4.2 Important symptoms and effects which are acute or occur with a delay

No information is available.

4.3 Indication of any immediate medical attention and special treatment needed

No information is available.

5. FIREFIGHTING MEASURES

5.1 Extinguishing agents

Suitable extinguishing agents Alcohol resistant foam, extinguishing powder, carbon dioxide, fine

water spray

Unsuitable extinguishing

agents

Direct water jet

5.2 Particular risks associated with the material or mixture

Danger of bursting. In the event of a fire, it is possible that hazardous gases may be formed.

5.3 Information on fire fighting

Special protective equipment for firefighting:

In the presence of combustion or carbonization gases, any firefighting, rescue and clearing up activities should be undertaken only with heavy-duty respiratory protection.



Print date: 02/03/2016 Page 5

Revised:23.07.2015

Cimco-Werkzeugfabrik Carl Jul. Müller GmbH & Co. KG

Further information:

Cool endangered containers with water spray jet.

6. MEASURES IN THE EVENT OF ACCIDENTAL RELEASE

6.1 Person-related safety precautions, protective equipment and procedures to be followed in emergencies

Ensure sufficient ventilation.
Use personal protective clothing.

6.2 Environmental protection measures

If surface water or sewage system are contaminated, inform the responsible authorities.

Do not allow to enter the sewage system or ground water.

Do not allow to enter sewage system / surface water / ground water.

6.3 Methods and material for containment and cleaning

Absorb with suitable liquid-binding materials.

Dispose of the absorbed material in accordance with the regulations.

6.4 References to other sections

Safe handling: see section 7 Disposal: see section 13

Personal protective equipment: see section 8

7. HANDLING AND STORAGE

7.1 Safety measures for safe handling

Information on safe handling Extraction in enclosed spaces at floor height.

Ensure good room ventilation, extraction at the workplace where

necessary.

General protection measures Avoid contact with the eyes and skin.

Do not inhale gases / vapours / aerosols.

Hygiene measures Do not eat, drink or smoke while working.

Wash hands before breaks and after finishing work.

Information on fire and explosion

protection

Keep away from ignition sources – Do not smoke. Do not spray onto flames or incandescent materials.



Print date: 02/03/2016 Page 6

Revised:23.07.2015

Cimco-Werkzeugfabrik Carl Jul. Müller GmbH & Co. KG

Pressurised container.

Do not force open or incinerate after use

Together with air, vapours can form an explosive mixture. Take measures to protect against electrostatic charges.

Avoid exposure to heat.

7.2 Conditions for safe storage taking incompatibilities into consideration

Storage requirements Keep sealed in original packaging.

The local authority regulations for storage of aerosol dispensers

are to be observed.

Information on storage with other

products

Further information on storage

conditions

Protect against heat and direct sunlight.

The storage temperature must not exceed 50 °C. Keep container in a cool, well-ventilated place.

Storage class 2B

7.3 Specific end use

See section 1.2

8. LIMITATION AND MONITORING OF EXPOSURE / PERSONAL PROTECTIVE EQUIPMENT

8.1 Limit values

CAS No.	Designation	Type	[mg/m3]	[ppm]	Peak limit	Note
106-97-8	Butane	8 hours	2400	1000	4(II)	DFG
74-98-6	Propane	8 hours	1800	1000	4(II)	DFG
95-63-6	1,2,4- trimethyl benzene	8 hours	100	20	2(II)	DFG, EU, Y

Occupational exposure limit values

CAS No. Designation Type [mg/m3] [ppm] Note 95-63-6 1,2,4-trimethyl 8 hours 100 20 benzene

Additional information

National and local legal provisions must be adhered to.



Print date: 02/03/2016 Page 7

Revised:23.07.2015

Cimco-Werkzeugfabrik Carl Jul. Müller GmbH & Co. KG

8.2 Limiting and monitoring exposure

Personal protective equipment

General protective and hygiene The usual regulations for handling chemicals needs to be

measures adhered to.

Do not breathe in dust/smoke/mist. Keep away from food, drink and animal feed. Do not smoke, eat or drink while working. Avoid contact with the eyes and skin. Wash hands before a

break and after finishing work.

Respiratory protection Respiratory protection in the event of insufficient extraction or

prolonged exposure.

Briefly filtration device, Filter A/P2

Hand protection Gloves (solvent resistant)

It is recommended to clarify the chemical resistance of the above-mentioned protective gloves for special applications with

the glove manufacturer. Gloves made of nitrile rubber

The type of chemical protection gloves is to be selected according to the concentration and quantity of hazardous

materials

at the specific workplace.

Eye protection Tight fitting safety glasses

Personal protection Protective workwear

Limiting and monitoring environmental

exposure

Sufficient ventilation.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on the basic physical and chemical properties

Form aerosol

Colour amber

Odour characteristic

Steam pressure 2100 hPa 20 °C

Relative density 0.715 g/cm³ 20 °C

Melting point / Freezing point - na -



Print date: 02/03/2016 Page 8

Cimco-Werkzeugfabrik

Carl Jul. Müller GmbH & Co. KG

Revised:23.07.2015

Explosive properties LEL: 0.6 vol. %

UEL: 10.9 Vol%

Self-ignition temperature The product is not spontaneously combustible.

Ignition point - na -

Flammability - na -

Oxidizing properties - na -

Solubility in / miscibility with - na -

Ignition temperature 270° C.

Solvent content 67.1 %

Solids content 7.4 %

9.2 Other information

No information is available.

10. STABILITY AND REACTIVITY

10.1 Reactivity

No information is available.

10.2 Chemical stability

No information is available.

10.3 Possible hazardous reactions

No known hazardous reactions.

10.4 Conditions to be avoided

Avoid exposure to heat.

Formation of explosive gas mixtures with air.



Print date: 02/03/2016 Page 9

Revised:23.07.2015

Cimco-Werkzeugfabrik Carl Jul. Müller GmbH & Co. KG

10.5 Incompatible materials

No information is available.

10.6 Dangerous decomposition processes

No decomposition when used as intended.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

LD50 acute oral	Value/Evaluation > 5000 mg/kg	Species Rat	Method	Note Naphtha
LD50 acute dermal	> 5000 mg/kg	Rabbit		Naphtha
LC50 acute for inhalation	4951 mg/m3 (4 h)	Rat		Naphtha
Skin irritation	not irritating			
Eye irritation	not irritating			
Sensitisation skin	not sensitising			

General comments

The product is to be handled with the care usual when handling chemicals. Other hazardous characteristics can not be ruled out.

12. ENVIRONMENTAL INFORMATION

12.1 Toxicity

Fish	Value/Evaluation LL/EL/IL50 > 1000 mg/l (96 h)	Species Oncorhynchus mykiss	Method	Note Naphtha
Water fleas (daphnia)	EL0 1000 mg/l (48 h)	Daphnia magna		Naphtha



Print date: 02/03/2016 Page 10

Revised:23.07.2015

Cimco-Werkzeugfabrik Carl Jul. Müller GmbH & Co. KG

12.2 Persistence and degradability

No information is available.

12.3 Bio accumulation potential

No information is available.

12.4 Mobility in the soil

No information is available.

12.5 Results of PBT and vPvB assessment

PBT Not applicable

vPvB Not applicable

12.6. Other harmful effects

Hazardous to drinking water even if only a small quantity escapes into the subsoil Do not allow uncontrolled release of the product into the environment.

The product must not enter any bodies of water or the sewage system or water treatment plants respectively.

13. INFORMATION ON DISPOSAL

Recommendation Disposal according to the local official regulations

Product Dispose of in accordance with local authority regulations.

Waste code 15 01 04 Packaging made of metal

15 01 10* Packaging which contains residue of hazardous substances or is contaminated by hazardous substances.

Waste marked with an asterisk (*) are classed as hazardous waste according to Directive 2008/98/EC on hazardous waste.

Unclean packaging Dispose of in accordance with local authority regulations.



Print date: 02/03/2016 Page 11
Revised:23.07.2015

Cimco-Werkzeugfabrik Carl Jul. Müller GmbH & Co. KG

14. INFORMATION ON TRANSPORT

	ADR/RID	IMDG	IATA-DGR
14.1 UN number	1950	1950	1950
14.2 Proper UN shipping name	COMPRESSED GAS PACKAGING	AEROSOLS	Aerosols, inflammable
14.3 Transport hazard class	2.1	2.1	2.1
14.4 Packaging group	-	-	-
14.5 Environmental hazards	no	no	no

14.6 Special preventive measures for the user

Caution: Gases

14.7 Bulk transport according to Appendix II of the MARPOL agreement 73/78 and according to the IBC code

Not applicable

Transport by land ADR/RID

Danger label 2.1 Tunnel restriction code D Classification code 5F

Transport as "Limited quantity" as per section 3.4 ADR

15. STATUTORY REGULATIONS

15.1 Regulations on safety, health and environmental protection / specific legal regulations for the material or the mixture

VOC guideline

Note

Daten separat anfragen / Request data separately.

National regulations:

Information on employment restrictions

The national laws regarding employment restrictions are to be observed.



Print date: 02/03/2016 Page 12

Revised:23.07.2015

Cimco-Werkzeugfabrik Carl Jul. Müller GmbH & Co. KG

Water hazard class 3 VwVwS Appendix 4

Highly water-polluting

Technical instructions (TA) air

Class III Section NK Proportion 50 - 75 %

Incident ordinance: Incident ordinance, Appendix I: part 1: No. 8 and 9b.

15.2 Chemical safety assessment

A chemical safety assessment for materials in this mixture have not been carried out.

16. OTHER INFORMATION

Recommended use and restrictions

Existing national and local laws regarding chemicals are to be observed. Nur für den gewerblichen Gebrauch. / For industrial use only.

Further information

E1111000

National special provisions need to be implemented by each user on their own responsibility! The information given is based on our current level of knowledge and serves to describe the product in terms of the safety precautions to be taken. It does not represent an assurance of properties of the product described.

Please pay attention to additional information! - Our safety data sheets have been prepared according to the valid EU guidelines WITHOUT taking into consideration any special national regulations regarding handling hazardous materials and chemicals.

EUH066	Repeated contact can cause rough or cracked skin.
H220	Extremely inflammable gas.
H226	Liquid and vapour inflammable.
H304	Can be fatal if swallowed or if it enters the respiratory tract.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Hazardous to health if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness and dizziness.
H411	Toxic for water organisms, with long-term effects.