

Printing date: 29.01.20	016	Page 1	
Revision:	29.01.2016		
Cimco-Werkzeugfabrik Carl Jul. Müller GmbH & Co. K(3		
1. Identification of the s	ubstance / mixt	ture and of the company / undertaking	
1.1 Product identifier			
Trade name	WET.PRC	OTECT e-nautic ArtNr. 151146/151147	
1.2 Relevant identified u Industrial uses		stance or mixture and uses advised against none ubstances as such or in preparations at industrial sites	
Professional uses	Public dor	main (administration, education, entertainment, services, craftsmen)	
1.3 Details of the suppli	er of the safety	data sheet	
Manufacturer/Supplier:	Hohenhao D-42855 I	Cimco Werkzeugfabrik Carl Jul. Müller GmbH & Co. KG Hohenhagener Straße 1 - 5 D-42855 Remscheid +49 (0) 21913718-01 Fax: +49 (0) 21913718-86	
1.4 Emergency telephone number Emergency CONTACT (24-Hour-Number) GBK GmbH +49 (0)6132-84463			

2. Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 1	H222-H229
Asp. Tox. 1	H304
Aquatic Chronic 3	H412

2.2 Label elements

• Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.



		/=000/=0; /
Printing date: 2	9.01.2016	Page 2
Revision:	29.01.2016	
Cimco-Werkzeugfabrik Carl Jul. Müller GmbH	& Co. KG	
JU.		
<u>(7</u>)		
GHS02	GHS08	
Signa	word	
Dange	r	

Danger

Hazard statements:

H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
11440	I leave ful to a supplie life with leave leating offerste

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251	Do not pierce or burn, even after use.
P273	Avoid release to the environment.
P211	Do not spray on an open flame or other ignition source.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331	Do NOT induce vomiting.
P405	Store locked up.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- vPvB: Not applicable



Printing date: 29.01.2016

Page 3

Revision:

29.01.2016

Cimco-Werkzeugfabrik Carl Jul. Müller GmbH & Co. KG

3. Composition/information on ingredients

Inhaltsstoffe	EINECS	CAS	Konzentrat [Gew-%]
entaromatisierte	265-150-3	64742-48-9	10-25
Kohlenwasserstoffe			Flam. Liq. 3, H226
			Asp. Tox. 1, H304
propane liquefied	200-827-9	74-98-6	10-25
			Flam. Gas 1, H220
			Press. Gas C, H280
butane, pure	203-448-7	106-97-8	10-25
-			Flam. Gas 1, H220
			Press. Gas c, H280
diphenyl tolyl phosphate	247-693-8	26444-49-5	<0,5
			Aquatic Acute 1, H400
			Aquatic Chronic 1, H410
2,6-di-tert-butyl-p-cresol	204-881-4	128-37-0	<0,5
			Aquatic Acute 1, H400
			Aquatic Chronic 1, H410

4. First aid measures

4.1 Description of first aid measures

General information	Instantly remove any clothing soiled by the product.
After inhalation	Supply fresh air; consult doctor in case of symptoms.
After skin contact	The product is generally no skin irritant.
After swallowing	Do not induce vomiting; instantly call for medical help.
After eye contact	Rinse opened eye for several minutes under running water.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.



Printing date: 29.01.2016		Page 4
Revision:	29.01.2016	
Cimco-Werkzeugfabrik Carl Jul. Müller GmbH & Co. KG		
5. Firefighting me	easures	

5.1 Extinguishing media

Suitable extinguishing agents Water spray jet

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for firefighters

Protective equipment:

Wear self-contained breathing apparatus.

6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions

Do not allow product to reach sewage system or water bodies.

6.3 Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to item 13. Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling See Section 8 for information on personal protection equipment. See Section 13 for information on disposal.

7. Handling and storage

7.1 Precautions for safe handling

No special precautions necessary if used correctly.



Printing date: 29.01.2016	Page 5	
Revision: 29.01.2016		
Cimco-Werkzeugfabrik Carl Jul. Müller GmbH & Co. KG		
Information about protection against explosions and fires	Beware: Container is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.	
7.2 Conditions for safe storage, including any incompatibilities		
Storage	Requirements to be met by storerooms and containers: Observe official regulations on storing packagings with pressurised containers.	
Information about storage in one common storage facility	Store away from oxidising agents.	
Further information about storage conditions	Keep container tightly sealed.	

7.3 Specific end use(s)

No further relevant information available.

8. Exposure controls/personal protection

8.1 Control parameters

Components with limit values that require monitoring at the workplace:

74-98-6 propane liquefied (10-25%)OEL (Ireland)Long-term value: 1000 ppm

And) Long-term value. 1000 Asphx

106-97-8 butane, pure (10-25%)

WEL (Great Britain)	Short-term value: 1810 mg/m ³ , 750 ppm
	Long-term value: 1450 mg/m ³ , 600 ppm
	Carc (if more than 0.1% of buta-1.3-diene)
OEL (Ireland)	Long-term value: 1000 ppm

Additional information: The lists that were valid during the compilation were used as basis.

8.2 Exposure controls

Personal protective equipment

General protective and hygienic	Keep away from foodstuffs, beverages and food.
measures	Wash hands during breaks and at the end of the work.



Printing date: 29.01.2016	Page 6		
Revision: 29.01.2016			
Cimco-Werkzeugfabrik Carl Jul. Müller GmbH & Co. KG			
Breathing equipment	Not required		
Protection of hands	The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.		
Eye protection	Not required.		

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	Aerosol
Colour	Colourless
Odou	Characteristic
Odour threshold	Not determined.
pH-value	Not determined.
Change in condition Melting point/Melting range Boiling point/Boiling range Flash point:	Not determined -44 °C -97 °C
Ignition temperature	> 200 °C
Decomposition temperature	Not determined.
Self-inflammability:	Product is not selfigniting.



Printing date: 29.01.2016 Page 7	
Revision: 29.01.2016	
Cimco-Werkzeugfabrik Carl Jul. Müller GmbH & Co. KG	
Danger of explosion	Not determined.
Critical values for explosion	
Lower:	0,6 Vol%
Upper:	10,9 Vol%
Vapour pressure at 20 °C:	ca. 8300 hPa
Density at 20 °C	Not determined.
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with Water:	Not determined.
Partition coefficient (n-octanol/water):	Not determined.
Viscosity:	
dynamic:	Not determined.
kinematic:	Not determined.
Solvent content:	
Organic solvents:	49,2 %
VOC - EU	48,88 %
VOC - EU	488,8 g/l
VOC - CH	
VOC - USA	285,0 g/l / 2,38 lb/gl
9.2 Other information	

No further relevant information available.

10. Stability and reactivity

10.1 Reactivity

No further relevant information available.

10.2 Chemical stability

No decomposition if used and stored according to specifications.

10.4 Conditions to avoid

No further relevant information available



Printing date:	29.01.2016	Page 8
Revision:	29.01.2016	
Cimco-Werkzeugfat Carl Jul. Müller Gmt	rik H & Co. KG	

10.5 Incompatible materials

No further relevant information available

10.6 Hazardous decomposition products

Inflammable gases/vapours

11. Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:

106-97-8 butane, pure

Inhalative LC50 (4 h) 658 mg/l (rat)

26444-49-5 diphenyl tolyl phosphate

Oral LD50 >5000 mg/kg (rat) Dermal LD50 >2000 mg/kg (rat)

128-37-02,6-di-tert-butyl-p-cresol

Oral LD50 2930 mg/kg (rat) Dermal LD50 >2000 mg/kg (rabbit)

Skin corrosion/irritation	Based on available data, the classification criteria are not met.
Serious eye damage/irritation	Based on available data, the classification criteria are not met.
Respiratory or skin sensitisation	 Based on available data, the classification criteria are not met. CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) Germ cell mutagenicity Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met. Reproductive toxicity Based on available data, the classification criteria are not met. STOT-single exposure Based on available data, the classification criteria are not met. STOT-repeated exposure Based on available data, the classification criteria are not met. Aspiration hazard May be fatal if swallowed and enters airways.



 Printing date:
 29.01.2016
 Page 9

 Revision:
 29.01.2016

 Cimco-Werkzeugfabrik Carl Jul. Müller GmbH & Co. KG

12. Ecological information

12.1 Toxicity

Aquatic toxicity:

26444-49-5 diphenyl tolyl phosphate

EC50 (96) 10 mg/l (Danio rerio) IC50 (72) 0,99 mg/l (Selenastrum capricornutum)

128-37-0 2,6-di-tert-butyl-p-cresol

LC50 (96h) > 0,42 mg/l (Brachydanio rerio) EC50 (75h) > 0,42 mg/l (Scenedesmus subspicatus) LC50 (48h) > 0,57 mg/l (Daphnia magna)

12.2 Persistence and degradability

Not easily biodegradable

12.3 Bioaccumulative potential

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

Additional ecological information:

General notes Water hazard class 2 (Self-assessment): hazardous for water.

12.5 Results of PBT and vPvB assessment

PBT	Not applicable
-----	----------------

vPvB Not applicable

12.6. Other adverse effects

No further relevant information available.

13. Disposal considerations

Waste treatment methods

Must not be disposed of together with household garbage. Do



Printing date: 29.01.2016		Pag	ge 10
Revision: 29.01.2016	5		
Cimco-Werkzeugfabrik Carl Jul. Müller GmbH & Co. KG			
	not allow product to	reach sewage system	
Uncleaned packagings	Disposal must be ma	ade according to officia	al regulations.
14. Transport information			
	ADR/RID	IMDG	IATA-DGR
14.1 UN- Number	1950	1950	1950
14.2 UN proper shipping	1950 AEROSOLS	AEROSOLS	Aerosols, flammable
name 14.3 Transport hazard	2 5F Gases	2.1	2.1
class(es) 14.4 Packing group	-	-	-
14.5 Environmental hazards	Not applicable	Not applicable	Not applicable
14.6 Special precautions for user			
Warning: Gases			
14.7 Transport in bulk according	to Annex II of Marpol and	the IBC Code	
Not applicable			
15. Regulatory information			
15.1 Safety, health and environm Directive 2012/18/EU Named dangerous substances - AN		-	bstance or mixture
Seveso category P3a FLAMMABLE AEROSOLS Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t			

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

National regulations

Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.



Printing date:	29.01.2016	Page 11
Revision:	29.01.2016	
Cimco-Werkzeugfab Carl Jul. Müller Gmb	rik H & Co. KG	

Technical instructions (air)

 Class
 Share in %

 III
 10-25 %

 NK
 25-50 %

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

16. Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- H220 Extremely flammable gas
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.